

[Back](#)[?](#)

Certification No
: GMA-511208-EA

Certifier : Glo

Applicant
: Mean Well Enterprises Co., Ltd.

Equipment Class
: Level 3 - Power Supply or Charger

Description
: Built-in Battery Charger

Certified Date: 12/20/2021

Expiry Date : **12/20/2026**

Standard: AS/NZS 60335.2.29:2017 & AS/NZS 60335.1:2020

Certification Conditions: - for use with lead acid and lithium batteries

Profiles

Model	Trade Name	Profile	
NPB-120-12AD1	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 14.4 Vdc 6.8 A Outputs
		Comments	
NPB-120-12TB	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 14.4 Vdc 6.8 A Outputs
		Comments	
NPB-120-12XLR	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 14.4 Vdc 6.8 A Outputs
		Comments	
NPB-120-24AD1	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 28.8 Vdc 4A Outputs
		Comments	

NPB-120-24TB	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 28.8 Vdc 4A	Outputs
		Comments		
NPB-120-24XLR	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 28.8 Vdc 4A	Outputs
		Comments		
NPB-120-48AD1	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 57.6 Vdc 2A	Outputs
		Comments		
NPB-120-48TB	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 57.6 Vdc 2A	Outputs
		Comments		
NPB-120-48XLR	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,1.5A Output: 57.6 Vdc 2A	Outputs
		Comments		
NPB-240-12AD1	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,3.0A Output: 14.4 Vdc 13,5 A	Outputs
		Comments		
NPB-240-12TB	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,3.0A Output: 14.4 Vdc 13,5 A	Outputs
		Comments		
NPB-240-12XLR	MEANWELL	Inputs	Input: 100-240V~,50/60Hz,3.0A Output: 14.4 Vdc 13,5 A	Outputs
		Comments		

NPB- 240- 24AD1	MEANWELL	Inputs	Input: 100- 240V~,50/60Hz,3.0A Output: 28.8 Vdc 8A	Outputs
		Comments		
NPB- 240- 24TB	MEANWELL	Inputs	Input: 100- 240V~,50/60Hz,3.0A Output: 28.8 Vdc 8A	Outputs
		Comments		
NPB- 240- 24XLR	MEANWELL	Inputs	Input: 100- 240V~,50/60Hz,3.0A Output: 28.8 Vdc 8A	Outputs
		Comments		
NPB- 240- 48AD1	MEANWELL	Inputs	Input: 100- 240V~,50/60Hz,3.0A Output: 57.6 Vdc 4A	Outputs
		Comments		
NPB- 240- 48TB	MEANWELL	Inputs	Input: 100- 240V~,50/60Hz,3.0A Output: 57.6 Vdc 4A	Outputs
		Comments		
NPB- 240- 48XLR	MEANWELL	Inputs	Input: 100- 240V~,50/60Hz,3.0A Output: 57.6 Vdc 4A	Outputs
		Comments		
NPB- 360- 12AD1	MEANWELL	Inputs	Input:100- 240V~,50/60Hz,4.5A Output: 14.4 Vdc 20	Outputs
		Comments		
NPB- 360- 12TB	MEANWELL	Inputs	Input:100- 240V~,50/60Hz,4.5A Output: 14.4 Vdc 20	Outputs
		Comments		
NPB- 360- 12XLR	MEANWELL	Inputs	Input:100- 240V~,50/60Hz,4.5A Output: 14.4 Vdc 20	Outputs
		Comments		

NPB- MEANWELL **Inputs** Input:100- **Outputs**
360- 240V~,50/60Hz,4.5A
24TB Output: 28.8 Vdc 12A

Comments

NPB- MEANWELL **Inputs** Input:100- **Outputs**
360- 240V~,50/60Hz,4.5A
24XLR Output: 28.8 Vdc 12A

Comments

NPB- MEANWELL **Inputs** Input:100- **Outputs**
360- 240V~,50/60Hz,4.5A
24AD1 Output: 28.8 Vdc 12A

Comments

NPB- MEANWELL **Inputs** Input:100- **Outputs**
360- 240V~,50/60Hz,4.5A
48AD1 Output: 57.6 Vdc 6A

Comments

NPB- MEANWELL **Inputs** Input:100- **Outputs**
360- 240V~,50/60Hz,4.5A
48TB Output: 57.6 Vdc 6A

Comments

NPB- MEANWELL **Inputs** Input:100- **Outputs**
360- 240V~,50/60Hz,4.5A
48XLR Output: 57.6 Vdc 6A

Comments

Version 1.1 Last Updated: 11 April, 2022

© Copyright State of Victoria | [Disclaimer](#) | [Privacy Statement](#) | [State Government of Victoria Home](#) |