



Mean Well DC UPS Models

MEAN WELL's DC UPS power supplies available in both Enclosed and DIN Rail style and suitable for 12V, 24V, 36V and 48V Lead Acid and Li-Ion battery systems. Featuring Low Battery, Reverse Connection and AC OK alarm signals they are perfect for critical battery back-up applications for monitoring, security, fire or industrial automation systems. These are RCM approved and have a 3 year warranty.

Model

(Click link to see full spec)

Specifications

Size

(L x W x H)

Model





(Click link to see full spec)

Specifications

Size

(L x W x H)

Enclosed Versions

	LAD-120A	120W, 13.8V, 7.7A	140x63x32 mm		LAD-240A	240W, 13.8V, 16.4A	215x115x30 mm
	LAD-120B	120W, 27.6V, 3.4A			LAD-240B	240W, 27.6V, 7.7A	
	LAD-120C	120W, 41.5V, 1.9A			LAD-240C	240W, 41.5V, 4.78A	
	LAD-120D	120W, 55.2V, 1.21A			LAD-240D	240W, 55.2V, 3.4A	
	LAD-360B	360W, 27.4V, 11.5A	215x115x30 mm		LAD-600B	600W, 27.6V, 18.7A	225x124x41 mm
	LAD-360C	360W, 41.5V, 7.14A			LAD-600C	600W, 41.5V, 11.45A	
	LAD-360D	360W, 55.2V, 5.03A			LAD-600D	600W, 55.2V, 7.87A	

Din Rail Versions

	DRC-40A	40W, 12V, 1.9A	40x90x100 mm		DRC-60A	60W, 12V, 2.8A	40x90x100 mm
	DRC-40B	40W, 24V, 1A			DRC-60B	60W, 24V, 1.5A	
	DRC-100A	100W, 12V, 4.5A	55x90x100 mm		DRC-180A	180W, 12V, 9A	63x125.2x115 mm
	DRC-100B	100W, 24V, 2.25A			DRC-180B	180W, 24V, 4.5A	